

# PRODUCT SPECIFICATIONS

<b>Product Family</b>	CLINiC Telehealth Videoconferencing
<b>Part Number</b>	CLINiC-C-12X27-B01
<b>Codec</b>	Cisco WebEx Roomkit Plus
<b>Camera</b>	Sony SRG-120DH camera 12X optical/12X digital zoom
<b>Display</b>	<ul style="list-style-type: none"> <li>• 27" IPS LED</li> <li>• 2560 x 1440 Native Resolution</li> <li>• 178° Viewing Angle</li> <li>• 5 ms Response Time</li> </ul>
<b>Tactile Control Panel</b>	<ul style="list-style-type: none"> <li>• AutoDial/Connect</li> <li>• Disconnect</li> <li>• Camera Pan/Tilt/Zoom</li> <li>• Self-View (Secondary Function: Display Layout)</li> <li>• Camera Mute (with LED indicator)</li> <li>• Microphone Mute (with LED indicator)</li> <li>• PC Source Selection (with LED indicator)</li> <li>• Horus Scope Source Selection (with LED indicator)</li> <li>• Volume Up/Down</li> <li>• Stethoscope Mode (with LED indicator)</li> <li>• Headphone Mode (with LED indicator)</li> <li>• "On-Air" LED Indicator</li> </ul>
<b>Remote Control Port</b>	RJ45 for optional Cisco Touch 10 Control panel
<b>Auxiliary Ports</b>	<ul style="list-style-type: none"> <li>• DB9 expansion control port (for future use)</li> <li>• Dual USB 3 Ports on display for powering optional accessories</li> <li>• System USB 3 Port (Supplied with blanking cover - Future use)</li> <li>• Codec maintenance Port (For qualified engineering usage)</li> </ul>
<b>Network</b>	<ul style="list-style-type: none"> <li>• 1 x 10/100/1G Ethernet</li> <li>• Wi-Fi capable (Requires optional Cisco Touch 10 controller to configure)</li> </ul>
<b>Video Inputs</b>	<ul style="list-style-type: none"> <li>• Sony SRG-120DH camera 12x optical/12x digital zoom</li> <li>• 1 x HDMI designated for PC Input</li> <li>• 1 x HDMI designated for Horus Scope Input</li> </ul>
<b>Video Output</b>	1 x HDMI (dedicated to display)
<b>Audio Input</b>	<ul style="list-style-type: none"> <li>• Integrated microphone</li> <li>• 1 x 3.5mm 3 pole, front mounted, for electronic stethoscope</li> <li>• 1 x 3.5mm 4 pole includes phantom power for Auxiliary Cisco Microphone</li> </ul>
<b>Audio Output</b>	<ul style="list-style-type: none"> <li>• Integrated stereo speakers; 2 x 5 Watts</li> <li>• 1 x 3.5mm (for headphone)</li> </ul>
<b>Dimensions (includes camera)</b>	<ul style="list-style-type: none"> <li>• 24" Wide</li> <li>• 21" High (Detachable Speaker Deflector adds 1.25")</li> <li>• 5.5" Deep</li> </ul>
<b>Weight</b>	28.7 lbs
<b>Mounting</b>	Compatible with 100mm x 100mm VESA mounts
<b>Electrical</b>	<ul style="list-style-type: none"> <li>• 100-240V-50/60Hz, 2.1A - 1.05A</li> <li>• Integrated auto sensing power supply</li> <li>• 1 x IEC type inlet</li> </ul>

# PRODUCT SPECIFICATIONS

